Airpush Variety1

Host App

MAIN

Main

BOOT

BootReceiver

Start SDK

Restart SDK

AirPush

Schedule

UserDetailsReceiver

MessageReceiver

http://api.airpush.com/model/user/getappinfo.php?

Send: package name
Receive: app info

Restart SDK

PushService

Send type "message"

Send type "userinfo"

If get action 1 - 4
send the adType
and type to
PushService.

DeliveryReceiver

PushService tasks:
type:
1. message: communicate with server and get new task via json. Including target number, url, sms text to send, etc. Insert bookmarks for the browser, and create ad shortcut in the home screen.
2. userinfo: upload device info, gps, phone number, gmail, etc.
3. delivery: send adType: CC, CM, W, A with required phone number, sms, url to PushAds.

update

PushAds

http://api.airpush.com/v2/api.php

PushAds tasks:
CC: open dial app and fill in phone number to call.
CM: open sms app and fill in target number and sms to send.
W: display url in the webview
A: display market url in the webview
BPCC, BPCM, BPW, BPA.
Here BP means **BannerPush,** it doing similar things as CC, CM … but show in the banner.

Receive Actions	Send adType	Send type
setDeliveryReceiverPhone	CC	delivery
setDeliveryReceiverSMS	CM	delivery
setDeliveryReceiverWEB	W	delivery
setDeliveryReceiverMARKET	A	delivery
setIconReceiver		